

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)
Unique Formula Identifier : K1P3-6Y4F-E50U-PE9A, KWE6-AYCE-Q50Q-5T0U, VR69-FYKE-050M-N5RC

1.2 Relevant identified uses of the substance or mixture and uses advised against

No information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier : Lascaux Colours & Restauro, Barbara Diethelm AG
Street : Zürichstrasse 42
Postal code/City : CH-8306 Brüttisellen
Telephone : +41 44 807 41 41
Telefax : +41 44 807 41 40
Information contact : Lab, +41 44 807 41 42, labor.swiss@lascaux.ch
European address : Lascaux Colours & Restauro Europe GmbH
Street : Turmstrasse 11
Postal code/City : D-78467 Konstanz
Telephone : +49 7531 911 3996
Telefax : +49 7531 911 3997
Information contact : Lab, +41 44 807 41 42, labor.swiss@lascaux.ch

1.4 Emergency telephone number

Tox Info Suisse, 24-h-emergency number 145, Tel. +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 2 ; H229 - Aerosols : Category 2 ; Pressurised container: May burst if heated.
Aerosol 2 ; H223 - Aerosols : Category 2 ; Flammable aerosol.
Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.
STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

N-BUTYL ACETATE ; CAS No. : 123-86-4
PROPAN-2-OL ; CAS No. : 67-63-0

Hazard statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

H223 Flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P312 Call a POISON CENTER/doctor/... if you feel unwell.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container to

Additional information

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

PROPANE ; EC No. : 200-827-9; CAS No. : 74-98-6

Weight fraction : $\geq 1 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280

N-BUTYL ACETATE ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction : $\geq 20 - < 25 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066

PROPAN-2-OL ; EC No. : 200-661-7; CAS No. : 67-63-0

Weight fraction : $\geq 15 - < 20 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

BUTAN ; CAS No. : 106-97-8

Weight fraction : $\geq 10 - < 15 \%$
Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Comp.) ; H280

DIMETHYL ETHER ; EC No. : 204-065-8; CAS No. : 115-10-6

Weight fraction : $\geq 5 - < 10 \%$
Classification 1272/2008 [CLP] : Flam. Gas 1 ; H220 Press. Gas (Liq.) ; H280
Substance with a community workplace exposure limit

2-METHOXY-1-METHYLETHYL ACETATE ; EC No. : 203-603-9; CAS No. : 108-65-6

Weight fraction : $\geq 5 - < 10 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Irrit. 2 ; H319

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Trade name :	Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)	Version (Revision) :	6.0.0 (5.0.0)
Revision date :	15.05.2024		
Print date :	15.05.2024		

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Following inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

In case of skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

Following ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

Appropriate breathing apparatus may be required.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8. Gas mask in case of spray processing.

Protective measures

Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510) (D) : 2B

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking. Keep containers dry and cool. Keep containers in a well-ventilated place. Comply with the health and safety at work laws.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : MAK (CH)

Limit value : 240 mg/m³ / 50 ppm

Remark : SSC

Version : 31.01.2022

Limit value type (country of origin) : STEL (CH)

Limit value : 720 mg/m³ / 150 ppm

Remark : SSC

Version : 31.01.2022

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 62 ppm / 300 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)

Limit value : 150 ppm / 723 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)
Revision date : 15.05.2024 **Version (Revision) :** 6.0.0 (5.0.0)
Print date : 15.05.2024

Version : 20.06.2019
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 241 mg/m³
Version : 20.06.2019
PROPAN-2-OL ; CAS No. : 67-63-0
Limit value type (country of origin) : MAK (CH)
Limit value : 500 mg/m³ / 200 ppm
Remark : SSC B
Version : 31.01.2022
Limit value type (country of origin) : STEL (CH)
Limit value : 1000 mg/m³ / 400 ppm
Remark : SSC B
Version : 31.01.2022
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 200 ppm / 500 mg/m³
Peak limitation : 2(II)
Remark : Y
Version : 23.06.2022
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Whole blood (B) / End of exposure or end of shift
Limit value : 25 mg/l
Version : 25.02.2022
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Urine (U) / End of exposure or end of shift
Limit value : 25 mg/l
Version : 25.02.2022
PROPANE ; CAS No. : 74-98-6
Limit value type (country of origin) : MAK (CH)
Limit value : 1800 mg/m³ / 1000 ppm
Version : 31.01.2022
Limit value type (country of origin) : STEL (CH)
Limit value : 7200 mg/m³ / 4000 ppm
Version : 31.01.2022
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1000 ppm / 1800 mg/m³
Peak limitation : 4(II)
Version : 23.06.2022
BUTAN ; CAS No. : 106-97-8
Limit value type (country of origin) : MAK (CH)
Limit value : 1900 mg/m³ / 800 ppm
Version : 31.01.2022
Limit value type (country of origin) : STEL (CH)
Limit value : 7600 mg/m³ / 3200 ppm
Version : 31.01.2022
DIMETHOXYMETHANE ; CAS No. : 109-87-5
Limit value type (country of origin) : MAK (CH)
Limit value : 3100 mg/m³ / 1000 ppm
Remark : SSC
Version : 31.01.2022
Limit value type (country of origin) : STEL (CH)
Limit value : 6200 mg/m³ / 2000 ppm
Remark : SSC

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)
Revision date : 15.05.2024 **Version (Revision) :** 6.0.0 (5.0.0)
Print date : 15.05.2024

Version : 31.01.2022
DIMETHYL ETHER ; CAS No. : 115-10-6
Limit value type (country of origin) : MAK (CH)
Limit value : 1910 mg/m³ / 1000 ppm
Version : 31.01.2022
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1000 ppm / 1900 mg/m³
Peak limitation : 8(II)
Version : 23.06.2022
Limit value type (country of origin) : TWA (EC)
Limit value : 1000 ppm / 1920 mg/m³
Version : 20.06.2019
2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6
Limit value type (country of origin) : MAK (CH)
Limit value : 275 mg/m³ / 50 ppm
Remark : SSC
Version : 31.01.2022
Limit value type (country of origin) : STEL (CH)
Limit value : 275 mg/m³ / 50 ppm
Remark : SSC
Version : 31.01.2022
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 270 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 06.11.2015
Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 550 mg/m³
Remark : H
Version : 08.06.2000
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 275 mg/m³
Remark : H
Version : 08.06.2000

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Use safety glasses.

Skin protection

Hand protection

Solvent-resistant protective gloves must be worn. For prolonged or repeated handling, use barrier creams to protect the exposed areas of the skin.

Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. After skin contact wash thoroughly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

Other protection measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Aerosol

Colour : Colourless

Odour

characteristic

Safety characteristics

Initial boiling point and boiling range :	(1013 hPa)	not applicable
Flash point :	approx.	-42 °C
Vapour pressure :	(50 °C) approx.	3 - 4 hPa
Density :	(20 °C) approx.	0.75 g/cm ³
Viscosity :	(20 °C)	not applicable

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity

Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	14 g/kg
Parameter :	LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route :	Oral
Species :	Rabbit
Effective dose :	7.4 g/kg

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

Parameter : LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Oral
Species : Rat
Effective dose : 5840 mg/kg
Parameter : LD50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route : Oral
Species : Rat
Effective dose : 8500 mg/kg

Acute inhalation toxicity

Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Exposure route : Inhalation
Species : Rat
Effective dose : 2000 ppm
Parameter : LC50 (2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6)
Exposure route : Inhalation
Species : Rat
Effective dose : 35.7 mg/l

11.2 Information on other hazards

Other adverse effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

There are no data available on the product itself. Do not empty into waters or drains.

SECTION 13: Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

13.1 Waste treatment methods

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Waste codes/waste designations according to EWC/AVV

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances.

SECTION 14: Transport information

14.1 UN number or ID number

UN 1950

14.2 UN proper shipping name

Land transport (ADR/RID)

AEROSOLS

Sea transport (IMDG)

AEROSOLS

Air transport (ICAO-TI / IATA-DGR)

AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 2
Classification code : 5F
Hazard identification number (Kemler No.) : 23
Tunnel restriction code : D
Special Provisions : LQ 1 I · E 0
Hazard label(s) : 2.1

Sea transport (IMDG)

Class(es) : 2.1
EmS-No. : F-D / S-U
Special Provisions : LQ 1 I · E 0
Hazard label(s) : 2.1

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 2.1
Special Provisions : E 0
Hazard label(s) : 2.1

14.4 Packing group

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux UV Protect 1, 2, 3 (2072, 2073, 2074)**
Revision date : 15.05.2024 Version (Revision) : 6.0.0 (5.0.0)
Print date : 15.05.2024

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 75

National regulations

U.S.A. Conforms to ASTM D-4236. "No health labeling required"

Water hazard class

Classification according to AwSV - Class (D) : 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Label elements - Additional information · 08. Occupational exposure limit values · 15. Restrictions on use · 15. Water hazard class

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.