according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date: 31.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Medium for Retouching (4140)

Unique Formula Identifier: 8XJY-M5AQ-A101-9SX8

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Synthetic Resin for the preservation and restoration of art and cultural assets

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier : Lascaux Colours & Restauro, Barbara Diethelm AG

 Street :
 Zürichstrasse 42

 Postal code/City :
 CH-8306
 Brüttisellen

 Telephone :
 +41 44 807 41 41

 Telefax :
 +41 44 807 41 40

Information contact :Lab, +41 44 807 41 42, labor.swiss@lascaux.chEuropean address :Lascaux Colours & Restauro Europe GmbH

 Street :
 Turmstrasse 11

 Postal code/City :
 D-78467
 Konstanz

 Telephone :
 +49 7531 911 3996

 Telefax :
 +49 7531 911 3997

Information contact: Lab, +41 44 807 41 42, labor.swiss@lascaux.ch

1.4 Emergency telephone number

Tox Info Suisse, 24-h-emergency number 145, Tel. +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2; H225 - Flammable liquids: Category 2; Highly flammable liquid and vapour. Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Flame (GHS02) : Exclamation mark (GHS07)

Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

Page: 1/9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date: 31.05.2023

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P337+P313 If eye irritation persists: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

2.3 Other hazards

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

ETHANOL ; EC No. : 200-578-6; CAS No. : 64-17-5 Weight fraction : \geq 40 - < 45 %

Classification 1272/2008 [CLP]: Flam. Liq. 2; H225 Eye Irrit. 2; H319

Specific Conc. Limits : Eye Irrit. 2 ; H319: $C \ge 50 \%$

ACETONE ; EC No. : 200-662-2; CAS No. : 67-64-1 Weight fraction : \geq 15 - < 20 %

Classification 1272/2008 [CLP]: Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Following inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

In case of skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

Following ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

Page: 2/9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 31.05.2023

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray.

Unsuitable extinguishing media

Waterjet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

Appropriate breathing apparatus may be required.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferabily with a detergent; avoid use of solvents.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8. Gas mask in case of spray processing.

Protective measures

Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical equipment should be pr.tected to the appropriate standard. Floors should be of the conducting type.

Hints on joint storage

Page: 3 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date: 31.05.2023

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510) (D): 3

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking. Keep containers dry and cool. Keep containers in a well-ventilated place. Comply with the health and saftey at work laws.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

ETHANOL; CAS No.: 64-17-5

Limit value type (country of origin): MAK (CH)

Limit value: 960 mg/m³ / 500 ppm

Remark: SSC
Version: 31.01.2022
Limit value type (country of origin): STEL (CH)

Limit value : 1920 mg/m³ / 1000 ppm

 Remark :
 SSC

 Version :
 31.01.2022

 Limit value type (country of origin) :
 TRGS 900 (D)

 Limit value :
 200 ppm / 380 mg/m³

Peak limitation: 4(II)

Remark : Y
Version : 23.06.2022

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin): MAK (CH)

Limit value: 1200 mg/m³ / 500 ppm

Remark: B
Version: 31.

 $\label{eq:Version:31.01.2022} \mbox{Limit value type (country of origin)}: \mbox{ STEL (CH)}$

 $Limit \ value: \qquad \qquad 2400 \ mg/m^3 \ \ / \ \ 1000 \ ppm$

Remark: B

 $\label{eq:Version: 31.01.2022} \mbox{ Limit value type (country of origin): TRGS 900 (D) }$

Limit value : $500 \text{ ppm} / 1200 \text{ mg/m}^3$

 Peak limitation:
 2(I)

 Remark:
 Y

 Version:
 23.06.

 $\label{eq:Version:23.06.2022} \mbox{Limit value type (country of origin)}: \mbox{ TRGS 903 (D)}$

Parameter : Acetone / Urine (U) / End of exposure or end of shift

 $\begin{array}{ll} \mbox{Limit value:} & 80 \mbox{ mg/l} \\ \mbox{Version:} & 25.02.2022 \\ \mbox{Limit value type (country of origin):} & TWA (EC) \end{array}$

Limit value : 500 ppm / 1210 mg/m³

Version: 20.06.2019

8.2 Exposure controls

Personal protection equipment

Page: 4/9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date: 31.05.2023

Eye/face protection

Use safety glasses.

Skin protection

Hand protection

Solvent-resistent protective gloves must be worn. For prolonged or repeated handling, use barrier creams to protect the exposed areas of the skin.

Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. After skin contact wash thorougly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

Other protection measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : resin

Colour : transparent

Odour : characteristic

Appearance

Physical state: Liquid

Colour : clear Odour

Poor, characteristic.

Safety characteristics

Initial boiling point and boiling (1013 hPa) approx. 56 °C range: °C Flash point: approx. -20 (50°C) Vapour pressure: 560 hPa approx. Density: (20°C) approx. 0.95 g/cm³ (20°C) Viscosity: mPa*s approx. 500

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

Page: 5 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 31.05.2023

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute oral toxicity

Parameter: LD50 (ETHANOL; CAS No.: 64-17-5)

Exposure route: Oral
Species: Rat
Effective dose: 21 a/kg

Parameter: LD50 (ETHANOL; CAS No.: 64-17-5)

Exposure route: Oral
Species: Rabbit
Effective dose: 6300 mg/kg

Parameter: LD50 (ACETONE ; CAS No. : 67-64-1)

Exposure route: Oral
Species: Rat
Effective dose: 9750 mg/kg

Acute dermal toxicity

Parameter: LD50 (ETHANOL; CAS No.: 64-17-5)

Exposure route: Dermal Species: Rabbit Effective dose: 20 g/kg

Parameter: LD50 (ACETONE ; CAS No. : 67-64-1)

Exposure route: Dermal Species: Rabbit Effective dose: 20 g/kg

11.2 Information on other hazards

Other adverse effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

Page: 6 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 31.05.2023

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

There are no data available on the product itself. Do not empty into waters or drains.

SECTION 13: Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Waste codes/waste designations according to EWC/AVV

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances.

SECTION 14: Transport information

14.1 UN number or ID number

UN 1866

14.2 UN proper shipping name

Land transport (ADR/RID)

RESIN SOLUTION

Sea transport (IMDG)

RESIN SOLUTION

Air transport (ICAO-TI / IATA-DGR)

RESIN SOLUTION

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 3
Classification code: F1
Hazard identification number (Kemler
No.): 33
Tunnel restriction code: D/E

Special Provisions: 640D · LQ 5 l · E 2

Hazard label(s): 3

Sea transport (IMDG)

 Class(es):
 3

 EmS-No.:
 F-E / S-E

 Special Provisions:
 LQ 5 | · E 2

 Hazard label(s):
 3

Air transport (ICAO-TI / IATA-DGR)

Class(es): 3
Special Provisions: E 2
Hazard label(s): 3

Page: 7 / 9

(EN / CH)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

Revision date: 31.05.2023 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 31.05.2023

14.4 Packing group

TT

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 3, 40, 75

National regulations

Water hazard class

Classification according to AwSV - Class (D): 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients · 08. Occupational exposure limit values

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

$^{16.4}$ Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

16.6 Training advice

None

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Page: 8 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Medium for Retouching (4140)

 Revision date:
 31.05.2023
 Version (Revision):
 5.0.0 (4.0.0)

 Print date:
 31.05.2023

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 9/9