

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Heat-Seal Adhesive 375 (4020)**
Revision date : 05.01.2023 Version (Revision) : 6.0.0 (5.0.0)
Print date : 11.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Lascaux Heat-Seal Adhesive 375 (4020)
Unique Formula Identifier : SSAW-G4AD-510X-3KT4

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Adhesives for the preservation and restoration of art and cultural assets

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier :

Lascaux Colours & Restauro, Barbara Diethelm AG

Street :

Zürichstrasse 42

Postal code/City :

CH-8306 Brüttisellen

Telephone :

+41 44 807 41 41

Telefax :

+41 44 807 41 40

Information contact :

info@lascaux.ch

European address :

Lascaux Colours & Restauro Europe GmbH

Street :

Turmstrasse 11

Postal code/City :

D-78467 Konstanz

Telephone :

+49 7531 911 3996

Telefax :

+49 7531 911 3997

Information contact :

Lab, +41 44 807 41 42, labor.swiss@lascaux.ch

1.4 Emergency telephone number

Tox Info Suisse, 24-h-emergency number 145, Tel. +41 44 251 51 51

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Repr. 2 ; H361d - Reproductive toxicity : Category 2 ; Suspected of damaging the unborn child.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Heat-Seal Adhesive 375 (4020)**

Revision date : 05.01.2023

Version (Revision) :

6.0.0 (5.0.0)

Print date : 11.05.2023

Danger

Hazard components for labelling

TOLUENE ; CAS No. : 108-88-3

NAPHTA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0

Hazard statements

H225	Highly flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

TOLUENE ; EC No. : 203-625-9; CAS No. : 108-88-3

Weight fraction : $\geq 35 - < 40$ %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 Repr. 2 ; H361d STOT RE 2 ; H373 Skin Irrit. 2 ; H315 STOT SE 3 ; H336

NAPHTA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0

Weight fraction : $\geq 20 - < 25$ %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Following inhalation

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name :	Lascaux Heat-Seal Adhesive 375 (4020)	Version (Revision) :	6.0.0 (5.0.0)
Revision date :	05.01.2023		
Print date :	11.05.2023		

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

In case of skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

Following ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters

Appropriate breathing apparatus may be required.

5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Heat-Seal Adhesive 375 (4020)**

Revision date : 05.01.2023

Version (Revision) : 6.0.0 (5.0.0)

Print date : 11.05.2023

7.1 Precautions for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8. Gas mask in case of spray processing.

Protective measures

Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type.

Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510) (D) : 3

Further information on storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking. Keep containers dry and cool. Keep containers in a well-ventilated place. Comply with the health and safety at work laws.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : MAK (CH)

Limit value : 190 mg/m³ / 50 ppm

Remark : H R2D R2F SSC OL B

Version : 31.01.2022

Limit value type (country of origin) : STEL (CH)

Limit value : 760 mg/m³ / 200 ppm

Remark : H R2D R2F SSC OL B

Version : 31.01.2022

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 50 ppm / 190 mg/m³

Peak limitation : 2(II)

Remark : H, Y

Version : 23.06.2022

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Toluene / Whole blood (B) / after end of exposure (h): 0

Limit value : 600 µg/l

Version : 25.02.2022

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Toluene / Urine (U) / End of exposure or end of shift

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Heat-Seal Adhesive 375 (4020)**

Revision date : 05.01.2023

Version (Revision) : 6.0.0 (5.0.0)

Print date : 11.05.2023

Limit value : 75 µg/l
Version : 25.02.2022
Limit value type (country of origin) : TRGS 903 (D)
O-cresol (after hydrolysis) / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts
Parameter :
Limit value : 1.5 mg/l
Version : 25.02.2022
Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 384 mg/m³
Remark : Skin
Version : 20.06.2019
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 192 mg/m³
Remark : Skin
Version : 20.06.2019

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Use safety glasses.

Skin protection

Hand protection

Solvent-resistant protective gloves must be worn. For prolonged or repeated handling, use barrier creams to protect the exposed areas of the skin.

Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. After skin contact wash thoroughly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

Other protection measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Pasty.

Colour : Whitish transpar.

Odour

Poor, characteristic.

Safety characteristics

Initial boiling point and boiling range :	(1013 hPa)	107 - 137 °C
Flash point :	>	6 °C
Vapour pressure :	(50 °C) approx.	35 hPa
Density :	(20 °C) approx.	0.84 g/cm ³
pH :		not applicable
Viscosity :	(20 °C) approx.	20000 mPa*s

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Heat-Seal Adhesive 375 (4020)**
Revision date : 05.01.2023 Version (Revision) : 6.0.0 (5.0.0)
Print date : 11.05.2023

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity

Parameter : LD50 (TOLUENE ; CAS No. : 108-88-3)
Exposure route : Oral
Species : Rat
Effective dose : 5000 mg/kg

Acute dermal toxicity

Parameter : LD50 (TOLUENE ; CAS No. : 108-88-3)
Exposure route : Dermal
Species : Rabbit
Effective dose : 14 g/kg

Acute inhalation toxicity

Parameter : LC50 (TOLUENE ; CAS No. : 108-88-3)
Exposure route : Inhalation
Species : Mouse
Effective dose : 5300 ppm

11.2 Information on other hazards

Other adverse effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lascaux Heat-Seal Adhesive 375 (4020)

Revision date : 05.01.2023

Version (Revision) : 6.0.0 (5.0.0)

Print date : 11.05.2023

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

There are no data available on the product itself. Do not empty into waters or drains.

SECTION 13: Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

13.1 Waste treatment methods

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Waste codes/waste designations according to EWC/AVV

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances.

SECTION 14: Transport information

14.1 UN number or ID number

UN 1133

14.2 UN proper shipping name

Land transport (ADR/RID)

ADHESIVES

Sea transport (IMDG)

ADHESIVES

Air transport (ICAO-TI / IATA-DGR)

ADHESIVES

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3

Classification code : F1

Hazard identification number (Kemler No.) : 33

Tunnel restriction code : D/E

Special Provisions : 640D · LQ 5 I · E 2 · ADR : III (<= 450 l)

Hazard label(s) : 3

Sea transport (IMDG)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : **Lascaux Heat-Seal Adhesive 375 (4020)**
Revision date : 05.01.2023 Version (Revision) : 6.0.0 (5.0.0)
Print date : 11.05.2023

Class(es) : 3
EmS-No. : F-E / S-D
Special Provisions : LQ 5 I · E 2 · IMDG 2.3.2.2 (Packing group III <= 450 l)
Hazard label(s) : 3
Air transport (ICAO-TI / IATA-DGR)
Class(es) : 3
Special Provisions : E 2 · IATA 3.3.3.1 (Packing group III <= 30 l)
Hazard label(s) : 3

14.4 Packing group

II

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40, 48, 75

National regulations

Technische Anleitung Luft (TA-Luft) (D) :

Weight fraction (Number 5.2.5. I) : 35 - 40 %

Water hazard class

Classification according to AwSV - Class (D) : 3 (Strongly hazardous to water)

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 15. Water hazard class

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lascaux Heat-Seal Adhesive 375 (4020)

Revision date : 05.01.2023

Version (Revision) : 6.0.0 (5.0.0)

Print date : 11.05.2023

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
